



Stirrer L

STIRRER FOR REVERBERATION CHAMBERS MODEL L




Figure 1




Figure 2

Technical specifications

Stirrer (see figure 1)	
Radius during rotation:	approx. 1980 mm
Length:	approx. 4100 mm
Edge length:	approx. 1400 mm
Stirrer mounted in vertical position (see figure 2)	
Max. length (motor+stirrer+counter bearing):	approx. 5500 mm
Min. length (motor+stirrer+counter bearing):	approx. 4800 mm
Position of the motor:	mounted on chamber ceiling
Other dimensions on request.	
Stirrer mounted in horizontal position on request	
Motor	
Stepping motor for high-precision angle setting	
For tuned and stirred mode	
Specified up to minimum 600 V/m continuous field strength	
Motor installed within the chamber (no influences on screening effectiveness of the room by stirrer motor shaft feed through)	
Positioning accuracy:	+/-0.5°
Angle resolution better:	0.1°
Min. speed:	0.5 turn/minute
Max. speed:	6 turns/minute
Dimension (L x W x H in mm):	350 x 272 x 250
Filter	
Typical attenuation 100 MHz to 1 GHz:	>100 dB
Typical attenuation 1 GHz to 10 GHz:	>100 dB
Typical attenuation 10 GHz to 18 GHz:	>80 dB
Dimension (L x W x H in mm):	210 x 130 x 53
Feed through:	Ø 21 mm
Motor control unit (mounted outside the chamber)	
Cable length between motor and control unit:	max. 10 m
Dimension (L x W x H in mm):	300 x 300 x 205
Supply:	110 to 230 V, 50 or 60 Hz
Power switch:	hardware switch
Communication interface to USO 4013:	opt. RS232
Connection:	2x HFBR0501 socket for 1 mm fiber optic cable
Distance:	10 m (>10 m on request)




Stirrer L STIRRER FOR REVERBERATION CHAMBERS MODEL L



Environment conditions

Classification:	Indoor use only
Operating temperature:	+5 °C to +40 °C
Relative humidity:	up to 80% (no moisture condensation)

System overview



Model No. and options

253352	RC Stirrer L Stirrer size L, remote controlled, incl. gear motor for step-wise and continuous rotation, positioning accuracy +/- 0.5°, smallest step 0.1°, motor installed inside chamber, the motor is installed inside the chamber, specified up to 600 V/m, incl. EMC filter, cables and stirrer control unit with remote interface and driver for C5I software
--------	---